

Storm D5 Series

BED WIDTH	BED LENGTH	AXLES CONFIGURATION	LOAD CAPACITY
60 in – 72 in – 82 in	10 ft – 12 ft – 14 ft	1 x 5,200 lb – 2 x 3,500 lb – 2 x 5,200 lb – 2 x 7,000 lb	2,800 lb – 11,190 lb



STOD5-612G205

STANDARD FEATURES

1	Telescopic cylinder (3-stage) – 7 tons (10 ft or 12 ft models), 12 tons (14 ft model)	8	All-round LED lighting
2	Aluminium toolbox N&N Smart Charger (15 A) 12 V deep cycle battery	9	Galvanized axles with electric brakes Radial tires on galvanized rims Slipper spring suspension
3	2 5/16 in adjustable coupler (5 positions)	10	14 ga galvanized N&N checker plate fenders
4	Low-temperature flexible wiring (Voltflex - made in Canada)	11	11 ga galvanized steel box 4 x 5/8 in D-rings welded to the box floor
5	7,000 lb N&N drop-leg jack Zinc-plated	12	Dual-action door (barn-door style & spreader)
6	Frame tubing: 2 x 5 x 3/16 in Cross members at 16 in centers Fully welded frame	13	Wood plank holder on each side
7	Precision laser-cut footstep (driver's side)	14	Tarp and roller with aluminum checker plate cover

MODEL UPGRADE (ADD OR COMBINE)



G-SERIES
Gas-powered hydraulic unit
13 HP



H-SERIES
Front hydraulic jack
12,000 lb capacity



L-SERIES (Landscape gate)
72 in model: 8,500 lb | 82 in model: 10,500 lb
Includes: 4 in drop axle and 36 in rear stabilizer legs

STORM D5 SERIES



OPTIONAL FEATURES (ADD-ON)



Aluminum
spring-assisted tarp



36 in rear
stabilizer legs



Wireless remote
for hydraulic unit



Galvanized 15 in x 72 in ramps | 10,000 lb
capacity | Stores underneath



Spare tire holder
(bolt-on)

DIMENSIONS

MODEL	5 ft x 10 ft	6 ft x 10 ft	6 ft x 12 ft	7 ft x 12 ft	7 ft x 14 ft
Overall width	80 in / 208 cm	94 in / 239 cm	94 in / 239 cm	102 in / 259 cm	102 in / 259 cm
Overall length	180 in / 457 cm	180 in / 457 cm	205 in / 521 cm	205 in / 521 cm	228 in / 579 cm
Usable width	60 in / 152 cm	72 in / 183 cm	72 in / 183 cm	82 in / 208 cm	82 in / 208 cm
Usable length	120 in / 305 cm	120 in / 305 cm	145 in / 368 cm	145 in / 368 cm	168 in / 427 cm
Bed height (landscape series)	26.5 in / 67 cm				
Floor thickness	11 ga / 3.13 mm				
Box height (front)	28 in / 71 cm				
Box height (sides)	18 in / 46 cm				
Box height (rear)	32 in / 81 cm				

AXLES CONFIGURATION

1 x 5,200 lb (2,359 kg) AXLE		STOD5-510G105			
Trailer weight	2,400 lb / 1,089 kg				
Load capacity	2,800 lb / 1,270 kg				
Tire size	225/75R15 8 ply				
Gross Vehicle Weight Rating (GVWR)	5,200 lb / 2,359 kg				
2 x 3,500 lb (1,588 kg) AXLES		STOD5-510G235			
Trailer weight	2,600 lb / 1,179 kg				
Load capacity	4,400 lb / 1,996 kg				
Tire size	205/75R14 6 ply				
Gross Vehicle Weight Rating (GVWR)	7,000 lb / 3,175 kg				
2 x 5,200 lb (2,359 kg) AXLES		STOD5-510G205	STOD5-610G205	STOD5-612G205	STOD5-712G205
Trailer weight	2,600 lb / 1,179 kg	2,900 lb / 1,315 kg	3,100 lb / 1,406 kg	3,350 lb / 1,520 kg	
Load capacity	7,300 lb / 3,311 kg	7,000 lb / 3,175 kg	6,800 lb / 3,084 kg	6,550 lb / 2,971 kg	
Tire size	225/75R15 8 ply	225/75R15 8 ply	225/75R15 8 ply	225/75R15 8 ply	
Gross Vehicle Weight Rating (GVWR)	9,900 lb / 4,491 kg				
2 x 7,000 lb (3,175 kg) AXLES		STOD5-714G207			
Trailer weight					3,810 lb / 1,728 kg
Load capacity					11,190 lb / 5,076 kg
Tire size					235/80R16 14 ply
Gross Vehicle Weight Rating (GVWR)					15,000 lb / 6,804 kg