

Torrent D6 Series

BED WIDTH

72 in – 82 in

BED LENGTH

12 ft – 14 ft – 16 ft

AXLES CONFIGURATION

2 x 7,000 lb – 2 x 8,000 lb – 2 x 10,000 lb – 3 x 7,000 lb – 3 x 8,000 lb

LOAD CAPACITY

9,925 lb – 15,880 lb

TORD6-712G207



STANDARD FEATURES

1 Telescopic cylinder (3-stage) – 7 tons (12 ft model), 12 tons (14 ft and 16 ft models)

2 Aluminium toolbox | N&N Smart Charger (15 A) | 12 V deep cycle battery

3 Quick connect for auxiliary 12V supply (14 ft or 16 ft models)

4 2 5/16 in adjustable coupler (5 positions)

5 12,000 lb N&N drop-leg jacks | Zinc-plated | Spring-assist return

6 Flexible low-temperature connection wiring (Volflex - made in Canada)

7 Precision laser-cut footstep (driver's side)

8 Frame tubing: 4 x 6 x 5/16 in | Cross members at 16 in centers | Fully welded frame

9 14 ga galvanized N&N checker plate fenders

10 Galvanized axles with electric brakes | Radial tires on galvanized rims | Slipper spring suspension | * 10,000 lb axles are not galvanized

11 Galvanized 15 in x 72 in ramps | 10,000 lb capacity | Stores underneath

12 All-round LED lighting

13 36 in rear stabilizer legs

14 Dual-action door (barn-door style & spreader)

15 11 ga galvanized steel box | 4 x 5/8 in D-rings welded to the box floor | * 7 ga galvanized floor (10,000 lb axle model)

16 Wood plank holder on each side

17 Tarp and roller with aluminum checker plate cover

MODEL UPGRADE (ADD OR COMBINE)



E-SERIES

Electro-hydraulic brake (1,200 psi)



G-SERIES

Gas-Powered Hydraulic Unit 13 HP



H-SERIES

Front hydraulic jack 12,000 lb capacity



L-SERIES (Landscape gate)

72 in model: 8,500 lb | 82 in model: 10,500 lb | Includes 4 in drop axle | *Only available on 7,000lb axles



T-SERIES

7 ga galvanized floor | Cross members at 12 in centers

TORRENT D6 SERIES



OPTIONAL FEATURES (ADD-ON)



Spare tire holder (bolt-on)



Wireless remote
for hydraulic unit



Aluminum spring-assisted tarp

DIMENSIONS

MODEL	6 ft x 12 ft	7 ft x 12 ft	7 ft x 14 ft	7 ft x 16 ft
Overall width	92 in / 234 cm	102 in / 259 cm	102 in / 259 cm	102 in / 259 cm
Overall length	205 in / 521 cm	205 in / 521 cm	228 in / 579 cm	252 in / 640 cm
Usable width	72 in / 183 cm	82 in / 208 cm	82 in / 208 cm	82 in / 208 cm
Usable length	145 in / 368 cm	145 in / 368 cm	168 in / 427 cm	192 in / 488 cm
Bed height	30 in / 76 cm	30 in / 76 cm	30 in / 76 cm	30 in / 76 cm
Bed height (landscape series)	26 in / 66 cm	26 in / 66 cm	26 in / 66 cm	26 in / 66 cm
Box thickness	11 ga / 3.13 mm	11 ga / 3.13 mm	11 ga / 3.13 mm	11 ga / 3.13 mm
Floor thickness (10,000 lb model)			7 ga / 4.65 mm	7 ga / 4.65 mm
Box height (front & rear)	32 in / 81 cm	32 in / 81 cm	32 in / 81 cm	32 in / 81 cm
Box height (sides)	23 in / 58 cm	23 in / 58 cm	23 in / 58 cm	23 in / 58 cm

AXLES CONFIGURATION

2 x 7,000 lb (3,175 kg) AXLES	TORD6-612G207	TORD6-712G207	TORD6-714G207	TORD6-716G207
Trailer weight	4,190 lb / 1,900 kg	4,465 lb / 2,025 kg	4,770 lb / 2,164 kg	5,075 lb / 2,302 kg
Load capacity	10,810 lb / 4,903 kg	10,535 lb / 4,779 kg	10,230 lb / 4,640 kg	9,925 lb / 4,502 kg
Tire size	235/80R16 14 ply	235/80R16 14 ply	235/80R16 14 ply	235/80R16 14 ply
Gross Vehicle Weight Rating (GVWR)	15,000 lb / 6,804 kg	15,000 lb / 6,804 kg	15,000 lb / 6,804 kg	15,000 lb / 6,804 kg

2 x 8,000 lb (3,629 kg) AXLES	TORD6-712G208	TORD6-714G208	TORD6-716G208
Trailer weight	4,615 lb / 2,093 kg	4,920 lb / 2,232 kg	5,225 lb / 2,370 kg
Load capacity	12,985 lb / 5,890 kg	12,680 lb / 5,752 kg	12,375 lb / 5,613 kg
Tire size	215/75R17.5 16 ply	215/75R17.5 16 ply	215/75R17.5 16 ply
Gross Vehicle Weight Rating (GVWR)	17,600 lb / 7,983 kg	17,600 lb / 7,983 kg	17,600 lb / 7,983 kg

3 x 7,000 lb (3,175 kg) AXLES	TORD6-716G307
Trailer weight	5,425 lb / 2,461 kg
Load capacity	15,575 lb / 7,065 kg
Tire size	235/80R16 14 ply
Gross Vehicle Weight Rating (GVWR)	21,000 lb / 9,525 kg

3 x 8,000 lb (3,629 kg) AXLES	TORD6-716G308
Trailer weight	5,700 lb / 2,585 kg
Load capacity	15,300 lb / 6,940 kg
Tire size	215/75R17.5 16 ply
Gross Vehicle Weight Rating (GVWR)	21,000 lb / 9,525 kg

2 x 10,000 lb (4,536 kg) AXLES	TORD6-714G210	TORD6-716G210
Trailer weight	5,120 lb / 2,322 kg	5,425 lb / 2,461 kg
Load capacity	15,880 lb / 7,203 kg	15,575 lb / 7,065 kg
Tire size	235/75R17.5 18 ply	235/75R17.5 18 ply
Gross Vehicle Weight Rating (GVWR)	21,000 lb / 9,525 kg	21,000 lb / 9,525 kg