

Lowland C6 Series

DECK WIDTH

80 in

DECK LENGTH

18 ft – 20 ft

AXLES CONFIGURATION

2 x 5,200 lb – 2 x 7,000 lb

LOAD CAPACITY

6,170 lb – 11,600 lb



LOWC6-720G207-H

shown with front hydraulic jack (model upgrade)

STANDARD FEATURES

| | | | |
|---|--|----|--|
| 1 | 2 5/16 in adjustable coupler (adjustable 5 positions) | 8 | 14,000 lb hydraulics cylinders (power up / gravity down) |
| 2 | Fully welded A-frame 2 x 6 x 3/16 in tubing | 9 | Deck Frame: 6 in C-channel Cross members at 16 in centers Fully welded frame |
| 3 | Stake pocket with rub rail | 10 | Welded winch plate |
| 4 | 4 in drop galvanized axles with electric brakes Radial tire on galvanized rims Slipper spring suspension | 11 | Low-temperature flexible wiring (Voltflex - made in Canada) |
| 5 | All-round LED lighting | 12 | Aluminium toolbox N&N smart charger (15 amp) 12 V deep cycle battery |
| 6 | 2 x 8 in hemlock floor 6 x 5/8 in D-ring welded | 13 | 12,000 lb N&N drop-leg jacks Zinc-plated Spring-assist return |
| 7 | 14 ga galvanized N&N checker plate fenders | | |



E-SERIES

Electro-hydraulic brake (1,200 psi)



H-SERIES

Front hydraulic jack



N-SERIES

Double acting cylinder & pump (power up / power down)



Spare tire holder (bolt-on)



Wireless remote for hydraulic unit

| MODEL | 7 ft x 18 ft | 7 ft x 20 ft |
|----------------|-----------------|-----------------|
| Overall width | 102 in / 259 cm | 102 in / 259 cm |
| Overall length | 288 in / 732 cm | 312 in / 792 cm |
| Usable width | 82 in / 208 cm | 82 in / 208 cm |
| Usable length | 218 in / 554 cm | 242 in / 615 cm |

| 2 x 5,200 lb (2,538 kg) AXLES (4 in DROP) | | LOWC6-718G205 | LOWC6-720G205 |
|---|--|---------------------|---------------------|
| Gross Vehicule Weight Rating (GVWR) | | 9,820 lb / 4,454 kg | 9,820 lb / 4,454 kg |
| Trailer weight | | 3,400 lb / 1,542 kg | 3,650 lb / 1,656 kg |
| Load capacity | | 6,420 lb / 2,912 kg | 6,170 lb / 2,799 kg |
| Tire size | | 225/75R15 8 ply | 225/75R15 8 ply |
| Deck height | | 21 in / 53 cm | 21 in / 53 cm |

| 2 x 7,000 lb (3,175 kg) AXLES (4 in DROP) | | LOWC6-718G207 | LOWC6-720G207 |
|---|--|----------------------|----------------------|
| Gross Vehicule Weight Rating (GVWR) | | 15,000 lb / 6,804 kg | 15,000 lb / 6,804 kg |
| Trailer weight | | 3,400 lb / 1,542 kg | 3,650 lb / 1,656 kg |
| Load capacity | | 11,600 lb / 5,262 kg | 11,350 lb / 5,148 kg |
| Tire size | | 235/80R16 14 ply | 235/80R16 14 ply |
| Deck height | | 21 in / 53 cm | 21 in / 53 cm |