

MODEL C8-IRONHD-20G16K



ADVANTAGE

FEATURES

- Entire welded structure
- 7 000 lb / 8 000 lb galvanised axles
- Tires 235-80R16 10 ply 6 holes galva. rim
- Standing ramp 24" x 60"
- 2 x 8 Hemlock floor
- 2" Slipper type leaf Spring
- 6 x Lashing Rings
- Rear stabilizing legs
- Width of 82" between the fenders
- Stake pockets with rub rail
- Voltflex Wiring cold weather harness
- Frame in channel 8"
- 2" metal descent with cleats
- Cross members on 16" C/C
- LED lights
- 2-5/16" adjustable coupler
- 12 000 lb "Drop Leg" Jack
- 27" Side Height
- Aluminum box on the front

TECHNICAL SPECIFICATIONS

USABLE WIDTH	82"
USABLE LENGTH	Floor 18' + 2' Drop
AXLES	2 x 8 000 lb electric
BRAKES	Electric
TIRES	215/75R17,5
WEIGHT WHEN EMPTY	4 300 lb
LOAD CAPACITY	13 300 lb
OVERALL LENGTH	292"
OVERALL WIDTH	102"
DECKING	Hemlock floor 2" x 8"
RAMP	24" x 60" Stand Up
FINISH	Hot dipped galvanised

