



MODEL C8-IRONHD-22G21K



ADVANTAGE

FEATURES

- Entire welded structure
- 7 000 lb / 8 000 lb galvanised axles
- Tires 235-80R16 10 ply 6 holes galva. rim
- Standing ramp 24" x 60"
- 2 x 8 Hemlock floor
- · 2" Slipper type leaf Spring
- 6 x Lashing Rings

- · Rear stabilizing legs
- · Width of 82" between the fenders
- Stake pockets with rub rail
- Voltflex Wiring cold weather harness
- Frame in channel 8"
- 2" metal descent with cleats

- Cross members on 16" C/C
- · LED lights
- 2-5/16" adjustable coupler
- 12 000 lb "Drop Leg" Jack
- 27" Side Height
- · Aluminum box on the front

TECHNICAL SPECIFICATIONS

USABLE WIDTH	82"
USABLE LENGTH	Floor 20' + 2' Drop
AXLES	3 x 7 000 lb electric
BRAKES	Electric
TIRES	235/80R16 10 ply
WEIGHT WHEN EMPTY	4 600 lb
LOAD CAPACITY	16 400 lb
OVERALL LENGTH	316"
OVERALL WIDTH	102"
DECKING	Hemlock floor 2" x 8"
RAMP	24" x 60" Stand Up
FINISH	Hot dipped galvanised







